Basic EDI import/export Process

- EDI connector (DigitalCAB) generates XML orders in C:\Moneyworks\Orders folder (one order per XML file)
- MW connector (Sussol) reads and. processes XML orders from C:\Moneyworks\Orders folder into MW. Orders successfully imported are moved to processed subfolder.
- MW connector (Sussol) checks for posted invoices in MW which have been modified since the timestamp of the last successful run, and exports XML invoices to C:\Moneyworks\Invoices folder (one XML file per invoice). If successful, update the timestamp (can be manually overridden if needed in MW connector settings).
- EDI connector (DigitalCAB) reads and processes XML invoices from C:\Moneyworks\Invoices folder.
- MW connector (Sussol) generates a log file each time it runs, in
 C:\MoneyworksConnector\Database\Logs (MW connector is a customised version of http://docs.sussol.net/doku.php/moneyworks:magento integration).

Notes

- The EDI format used by EDI connector contains data for the customer, invoice recipient, buyer and delivery recipient. Currently the buyer is modelled as the customer in MW e.g. "STARK.AA", where the head office has a code of "STARK.". For generating invoices, we have to also lookup and export the GLN/EAN for the head office.
- The customer GLN/EAN codes (name.custom1 in MW as name.code has only 11 characters) must be consistent across all systems. When importing an order, MW searches for a match on [Name.Custom1] import will fail if no match is found.
- The product GTIN codes ([Product.Barcode] in MW = <detail.stockcode> in XML) must be
 consistent across all systems importing an order will fail if no match is found. Note also that
 [Product.Code] (= [Detail.Stockcode]) in MW translates to <detail.supplierarticle> in XML,
 [Product.Custom1] (=TUN) in ME translates to <detail.manufacturerpart> in XML, and
 [Product.Custom2] in MW translates to <detail.buyerpart> in XML
- When importing orders, MW uses the account code of 1000 import will fail if that account code is missing.
- The tax rates and tax codes must be consistent across all systems import will fail if no match is found.

MW fields used

MW field	Data
transaction.ourref	invoice number
transaction.transdate	date of invoice
transaction.duedate	date payment is due
transaction.type	DII for invoice, SOI for order
transaction.theirref	customer's order number
transaction.namecode	customer code in MW
transaction.contra	account in MW
transaction.tofrom	use this for contact person
transaction.mailingaddress	always uses the customer's default mailing address

Last	update:	2014	/12	/16	12.09
Last					

transaction.deliveryaddress	use this for actual delivery address (NAD+DP) if supplied, otherwise the buyer's address (NAD+BY)			
transaction.salesperson	set to DD if using a direct delivery address			
transaction.flag	set to EDI for imported orders			
transaction.description	used to store the contact person as [ToFrom] gets wiped when sales order is processed			
transaction.analysis	supplier's order number			
transaction.user1	expected delivery date (yyyymmdd)			
transaction.user2	phone			
transaction.user3	email			
transaction.currency	currency - blank if default (DKK)			
transaction.freightdetails	freight details e.g. shipping code or number			
transaction.prodpricecode	A=DKK, B=SEK, C=NOK			
transaction.gross	gross total for transaction			
transaction.taxamount	tax total for transaction			
name.custom1	buyer's GLN/EAN (top level GLN/EAN looked up from corresponding head office name record)			
name.custom2	not used yet			
detail.account	sales account in MW			
detail.gross	line gross amount			
detail.tax	line VAT amount			
detail.net	line total before tax			
detail.description	product description			
detail.taxcode	tax code in MW			
detail.orderqty	quantity ordered			
detail.stockqty	quantity supplied			
detail.stockcode	product code (= supplier's article) - corresponds to <detail.supplierarticle> in XML</detail.supplierarticle>			
detail.unitprice	unit full price			
product.custom1	manufacturer's part number (=TUN) corresponds to <detail.manufacturerpart> in XML</detail.manufacturerpart>			
product.custom2	not used yet - corresponds to <detail.buyerpart> in XML</detail.buyerpart>			
product.barcode	product GTIN - corresponds to <detail.stockcode> in XML</detail.stockcode>			

Discounts for Ditas (XL-BYG) for EDI Orders

Script logic:

- When a sales invoice is opened... (on open window or whatever it's called)
 - o IF
- The customer code starts with: D and
- The flag field contains "EDI"
- There is no detail line the the code "RABATEDI" then:
 - Add a detail line that
 - Has the code RABATEDI
 - ∘ Has the quantity -1
 - $^{\circ}\,$ Has a price that is 1% of the total of the other lines (It gives 1% discount on invoices submitted to these customers via EDI

http://docs.sussol.net/ Printed on 2025/11/04 10:33

Pick List logic

Pick lists are split into 2 sections based on either shoe or accessories. Shoes have their product.category1 set to "Access" - that's it!

Shipping charges for customers

- 1. The number of pairs a customer must order in order to get free shipping is stored in name.custom4
- 2. As of Friday 04 July 2014 rates are
 - 1. 1 pair DKK 80,00
 - 2. 2 pairs DKK 100,00
 - 3. 3 pairs DKK 100,00
 - 4. 4 pairs DKK 100,00
 - 5. 5 pairs DKK 130,00
 - 6. 6 pairs DKK 130,00
 - 7. 7 pairs DKK 130,00
 - 8. 8 pairs DKK 130,00
 - 9. 9 pairs DKK 130,00
- 3. So if name.custom4 is "5" and customer orders 4 pairs they pay 100, if they order 5, they pay zero.

From:

http://docs.sussol.net/ - Sussol Docs

Permanent link:

http://docs.sussol.net/doku.php/moneyworks:edi?rev=1418731779

Last update: 2014/12/16 12:09

